

01-040-2004-0

01-040-3004-0

Auxiliary Foglight F650GS/ Dakar

Parts included:

1x auxiliary foglight including cables and relay
1x bracket for auxiliary foglight
1x bolt hex M5x10 LiKo
2x bolt hex M5x45 LiKo
4x washer for M5
4x washer for M6

2x bolt hex M6x10 LiKo
2x bolt hex M6x14 LiKo
1x spacer roll of 10.5.07
1x spacer roll of 10.5.19
1x spacer roll of 10.5.24
1x adapter ring eye 6.5
1x adapter flat pin



Do all electrical work with ignition switched off and battery disconnected!!

Assembly:


Remove seat, tank cover, windscreen and headlight. Attach the relay with the provided adhesive strip on the left in the headlight cowl (Photo 1).



Bring the yellow cable to the parking light cable and connect it with the provided adapter to grey/black cable and shorten to suitable length (Photo 2).



Bring the switch to the handlebar and install it at the left side directly beside the existing switch with the provided clamp, two screws LiKo M4x10 and two nuts M4. Adjust the switch position so that it can be flipped vertically. (Photo 3)
Bring the brown cable to negative pole of the battery. Shorten to suitable length and attach the cable to the round adapter eye. Do not connect yet.



01-040-2004-0

01-040-3004-0

Auxiliary Foglight

F650GS/ Dakar



Pull the red and blue cables to the right side of the upper covering. Install tank cover, side panels and headlight again. Bolt the fog headlight to the mounting plate with the two LiKo M6x14 bolts and washers. Bolt the fog headlight bracket to the right blinker mount with 2x LiKo M5x45, 1x LiKo M5x25 and the spacer rolls (24 in the back, 07 center, 19 in front). Bolt in the original screen screw connections (fig. 5).

Reattach screen with the LiKo M6x10 and washers.



Shorten the blue and red cable to correct lengths and pull them through the two paths planned for them to the lower part of the foglight rear cover. Attach the provided flat pins to the cables. Plug the blue cable into the foglight on the outside right. This is the ground wire.

Attach the red cable directly at the light. Bring the cover over the foglight. Attach the battery and the ground wire of the foglight. With parking light on the foglight should be able to be switched on now. Align the foglight and tighten all bolts. Screw the headlights onto the screen with the LiKo M6x10.

When assembling two fog headlights you need only one relay.
The assembly of the left side is identical to the right.

Pay attention that the cables cannot be severed or squeezed and are routed so that parts do not overheat. Secure all cables with cable straps, install tank cover and seat. The auxiliary headlight can be aligned by easily shifting it in the slotted hole in the mount.