

TOURATECH

TOURING RALLYE RACING TECHNOLOGY

April 2003

01-053-0055-0

Top Case Bracket R1150GS Adventure

Lieferumfang:

- 1 x Top Case Bracket premounted
- 1 x Adapterplate
- 1 x Mounting material

Mounting:

Remove the four screws as shown on the first photo.

Put the provided two plastic spacers on the front screws.


Lay the adapter plate on and use M6x45 screws and washers in the front and M6x70 screws and washers in the middle.

Use the M5x16 screws and washers and additional two larger washers and nuts in the back.

Now attach the topcase plate (with lock) on the adapter plate with the six counter sink screws and some locktite.



Use these instructions at your own risk. These instructions are new and have not been tested by independent installers. Touratech and Touratech-USA assume no responsibility for errors using these suggestions. If you have any doubts about your ability to install the panniers, please contact a professional installer.



TOURATECH

TOURING RALLYE RACING TECHNOLOGY

April 2003

01-053-0055-0

Top Case Bracket R1150GS Adventure

The x-shaped piece has 5 countersunk holes corresponding to holes in the plate that fastens to the bottom of the Zega case. The x-shaped piece goes inside the Zega case to reinforce the bottom of the case.

Center the plate on the bottom of the Zega Case, mark the 5 holes and drill to a diameter of 6.5 mm. Fasten with the 5 short machine screws countersunk on the bottom of the plate, the 5 large washers and 5 dome nuts on the inside of the Zega Case. Use locktite or similar thread locking compound.

To attach the Zega case to the rack, slide the 2 rectangular latches at the front of the case into the guides and pull the latch towards you. The box should fall flush with the rack and the latch plate should retract toward the front of the case. There is a break-in period until the latch loosens up a little. Turn the key to the right to lock. The lock must ALWAYS BE LOCKED when driving.

To remove the Zega case from the rack, see the first step above.

Consider the weight of the Zega case and contents when loading your motorcycle. Do not exceed the maximum load limits for the make and model of your motorcycle. DO NOT exceed 130km/h or about 78 MPH with the Zega case installed.

Use these instructions at your own risk. These instructions are new and have not been tested by independent installers. Touratech and Touratech-USA assume no responsibility for errors using these suggestions. If you have any doubts about your ability to install the panniers, please contact a professional installer.