## TOURING RALLYE RACING TECHNOLOGY

## 01-065-0077-0

Contains:

x Handlebar mount for GPS 60 preassembled
x Lanyard
x Cover for connector
x Key
Attachment plates and hardware for Garmin connector

Touratech GPS 60-series mount is designed to mount on dual sport type handlebars with 12mm or 1/2 inch cross Bar. Adapters are available for most other type handlebars

GPS mount is isolated with rubber mounts to give the best protection for your GPS. Make sure the GPS or the cradle are not touching handlebers or other motorcycle parts

## Installation Instruction: GPS 60 Handlebar Mount



Open the key lock in order to press the cradle open (1A). Set the GPS in the cradle and make sure the belt clip knob is installed on the back of the GPS. Round hole on the top of the mount (1B) will then engage around the knob and secure the GPS in the mount.



NOTE: install the power cord end on the mount first before routing the cable to +12V power source ! Special Garmin power cable is available for +12V power connection. Supplied attachment plates with M3x10 screws and nylock nuts are used to fix the power cord on the mount as seen on bottom right photo.

Make sure the connector is properly aligned in relation to the connector opening on the back of the GPS unit. Rubber cap over the power connection on the back of the unit can be removed.



Supplied rubber cap with lanyard can be used to cover power cord end when GPS is not in the mount.

Remove the batteries in offroad use or on highly vibrating motorcycles to avoid damage on the battery connections due vibration. Make sure mount and the GPS are securely attached prior to each ride !

Touratech mounts are designed and assembled with great care and attention to offer the best protection and convenience for the use of GPS on a motorcycle but damaged or lost GPS units are not subject to warranty claims.

These instructions are at our current level of knowledge. Technical issues subject to change. Legal requirements do not exist.